This Page Is Inserted by IFW Operations and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents will not correct images, please do not report the images to the Image Problem Mailbox.

EUROPEAN PATENT APPLICATION

(21) Application number: 95100159.3

(22) Date of filing: 07.01.95

(12)

(51) Int. Cl. 6: **B29C 70/24**, B29C 53/60,

B29C 53/68, B29D 23/00

30) Priority: 07.01.94 US 178664 03.02.94 US 191856

(43) Date of publication of application: 12.07.95 Bulletin 95/28

(84) Designated Contracting States: AT BE CH DE DK ES FR GB GR IE IT LI LU MC NL PT SE


(88) Date of deferred publication of search report: 15.11.95 Bulletin 95/46


(71) Applicant: COMPOSITE DEVELOPMENT CORPORATION 2380, Cranberry Highway West Wareham, Massachusetts 02576 (US) (72) Inventor: Quigley, Peter A. 94 Saltmarsh Lane Pocasset MA 02559 (US) Inventor: Noiet, Steven C. 2, Alexandria Drive,e Franklin Massachusetts 02038 (US) Inventor: Gallagher, James L 45 Hawkins Avenue Tiverton, RI 02878 (US)


(74) Representative : Blumbach, Kramer & Partner Patentanwälte Radeckestrasse 43 D-81245 München (DE)

(54) Composite shaft structure and manufacture.

The invention provides improvements to a composite member that has a plurality of plies. The improved composite member (10) has (1) an interior ply (12) which functions to dampen or resist sudden forces exerted on the composite member, (2) an intermediate load-carrying ply (14), and (3) an exterior abrasion-resistant ply (16). These plies have multiple, often intertwined fiber components disposed or imbedded with a matrix material, preferably Nylon-6 thermoplastic, to inhibit sharp edges during breakage. One or more of the plies typically has "bi-axial" or "tri-axially" braided fiber geometries wherein one or more fibers are helically wound about the circumference of the member. The helically oriented fibers are oriented at a selectively variable angle which influences the overall bending strength of the composite material. In one aspect, the angles of the fiber components and other factors are used to maintain substantially uniform cross-sectional area over the length of the tubular member while simultaneously varying the bending stiffness. In another aspect, the intermediate ply is constructed with two or more sub-plies. Such sub--plies can include tri-axially extending plies, and circumferentially-wound plies. The circumferentially-wound plies are often wound more tightly at the ends of the composite member to increase resistance to stresses caused by objects within the tubular shaft. A composite member constructed according to the invention resists sudden or impact forces and has high, selectively variable bending strength, high impact resistance, and safe failure modes.









EUROPEAN SEARCH REPORT

EP 95 10 0159

Category	Citation of document with of relevant p	indication, where appropriate,	Relevant te claim	CLASSIFICATION OF THE APPLICATION (Int.CL6)	
X Y	US-A-3 080 893 (D.	·	1-5 7,9, 13-17, 20-36	B29C70/24 B29C53/60 B29C53/68 B29D23/00	
	* column 2, line 37 - column 3, line 9 * * column 3, line 36 - line 53; figure 1 *		•		
Y	EP-A-0 470 896 (P. H. VIELLARD) * column 4, line 47 - column 5, line 4; figure 5 *		7,9,		
			20-36		
	* column 5, line 5 * column 7, line 2	- line 44; figure 6 * - line 10; figure 10 *	,		
X	FR-A-2 219 289 (W. * page 2, line 21 figures 2,5 *		1,7,13		
D,A	US-A-5 188 872 (P.	A. QUIGLEY)	1-6, 16-18,	TECHNICAL FIELDS	
	•		24,25, 27,28,	B29C (Int.CI.6)	
	* column 5, line 60 figure 1 *) - column 6, line 23;	30,31		
A	EP-A-0 402 309 (GEE	BR. SULZER AG.)	1,7, 10-19		
	column 3, line 16 - column 4, line 21; igures 1,2,6 *				
٨	FR-A-2 501 579 (TECHNIQUE DU VERRE TISSE) * the whole document *		1-8, 10-18		
		-/			
	The present search report has b				
	Plant of coarch	Date of completion of the search	05 5	Exemplair	
	THE HAGUE	11 September 19		gosi, A	
X : part Y : part éoct	CATEGORY OF CITED DOCUME icularly relevant if taken alone loaterly relevant if combined with an ment of the same category	E : earlier patient of after the filing other D : document cite	T: theory or principle underlying the invention E: extiler paint document, but published on, or after the filing date D: document cited in the application L: document cited for other reasons		
A: tech	nological background -written disclosure	å : manher of the			



EUROPEAN SEARCH REPORT

Application Number EP 95 10 0159

	DOCUMEN 12 COUST	DERED TO BE RELEVANT	' I	
Category	Citation of document with in of relevant pas	dication, where appropriate,	Relevant to claim	CLASSIFICATION OF THE APPLICATION (BLCLG)
A	EP-A-0 127 553 (TECH	1	1,6-8, 10-18, 20-34	
	* figures 2-4 * * column 6, line 15	- column 7, line 27 *	20 34	
	EP-A-O 204 607 (MANUELECTR. DE CAHORS) * column 2, line 27 * column 3, line 1 - * column 4, line 12	- line 45 *	9,35,36	
\	GB-A-1 305 198 (NAT) CORP.)	ONAL RESEARCH DEV.	30-34	
	* page 3, line 19 -	line 32; figure 4 *		
				TECHNICAL FIELDS SEARCHED (Inc.Cl.6)
<u></u>	The present search report has bee	o drawn up for all claims		
	Place of search	Date of completion of the search		Branday
	THE HAGUE	11 September 1995	Freg	osi, A
X : marti	ATEGORY OF CITED DOCUMENT culturly relevant if taken alone culturly relevant if combined with anoth	E : earlier patent docum	inderlying the is	evention

EPO FORM 15th that (Poscos)